

CF8M CF8 Screwed Threaded Pipe Fittings reducing coupling

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 10pcs
- Price:
- Packaging Details: Cartons+Ply-wooden cases, Pallets
- Delivery Time:
- Payment Terms: T/T, L/C, D/P
- Supply Ability:



Product Specification

Thread: DIN 2999, ISO 7/1, ISO 228, NPT, BSPT, BSP
Casting: Investment Casting
Material: 304/304L, 316/316L
Size: 1/4"-4"
Highlight: Screwed Threaded Pipe Fittings,

China

DEYE

STH-TH-22

ISO9001:2015 PED

USD0.5-USD50 for each pc

7 days for stock items

100000PCS one month

Threaded Pipe Fittings SS201, BSPT stainless steel npt fittings

SS201 SS304 SS316 50PSI NPT BSPT STAINLESS STEEL SCREWED THREADED PIPE FITTINGS

stainless steel pipe screw fittings are excellent for uses that involve chemicals or liquids that may be corrosive. Along with fighting corrosion, a stainless steel pipe fitting will prevent contamination making it useful to many professionals. 304 Stainless Steel is economically priced, chromium-nickel material that offers very good corrosion resistance. 316 Stainless Steel has higher nickel content and contains molybdenum for even better corrosion resistance

The screw types can NPT as per ASME B 1.20.1, BSPP BSPT as per BS21, DIN2999, The investment Stainless castings conform to ASTM A351 ACI Grade CF8 (304) & ACI Grade CF8M (316)

Product Information/Product Description/Basis Information/Specification

Description	CF8M CF8 Screwed Threaded Pipe Fittings reducing coupling
	threaded NPT BSPT 150PSI Elbows, Reducers, Coupling, Plug, Bushing, Union, Tee, cross, caps Stainless Steel Screwed Pipe Fittings Threaded Pipe Fittings Union, Hex Nipple, bushing, reducer socket, 45 90 degree elbow, Square Head plug, coupling, Y pipe joints tee
Size	1/2" 3/4" 1" 1-1/4" 1-1/2" 2" 2-1/2" 3" 4" 5" 6" 8"
Gasket	NBR, FKM
Thread	BSPT,BSPP, NPT,PS , DIN
Material	stainless steel201,202, stainless steel304, stainless steel 316
Casting Method	Investment precision casting, CNC machine
Application	Oil, Water, Industrial, Chemical
Test pressure	Usually 150PSI
Package	pcs/polybag, polybag/carton, cartons/pallet or according to your requirement
	1.OEM and Customized service can be provided
Advantages	2. With experience, quality guaranteed
nuvaniayes	3. Approved by ISO9001:2015
	With independent open mold capacity, OEM supposed

Technology/ Technical Data Sheets

Reducing Coupling	Hex. Bushing	Hose Nipple	

SIZE		C1	C2	SIZE	SIZE		C2
D1	D2	01	02	D1	D2	C1	02
1/8"	-	-	-	1-1/4"	1/8"-1	44	26
1/4"	1/8"	27	18	1-1/2"	1/8"-1-1/4"	48	29.5
3/8"	1/8"-1/4"	34	19	2"	1/8"-1-1/2"	56	32
1/2"	1/8"-3/8"	36	22	2-1/2"	1/8"-2"	62	36.5
3/4"	1/8"-1/2"	35	24	3"	1/8"-2-1/2"	67	37.5
1"	1/8"-3/4"	40	27	4"	1/8"-3"	76	42

Production Process



Common used Material Grade

SS316 Chemical Composition

ASTM A351 CF8M, SS316 Chemical Composition in %

ASTM A351 CF8M, SS316 Chemical Composition in %									
C Mn P S Si Ni Cr Mo									
Min.						9.0	18.0	2.00	
Max.	0.080	1.500	0.040	0.040	1.500	12.0	21.0	3.00	

SS316 Mechanical Properties of the Fittings at room temperature

	Tensile Strength Rm (N/mm2)	Upper Yield Point ReH (N/mm2) min.	Elongation at rupture A5 (%) min.	Hardness Test (HRB)
Min.	485	205	30	
Max.				80

SS304 Chemical Composition

ASTM A	ASTM A351 CF8, SS304 Chemical Composition in %									
	C Mn P S Si Ni Cr Mo									
Min.						8.0	18.0			
Max.	0.080	1.500	0.040	0.040	2.000	11.0	21.0	0.50		

SS304 Mechanical Properties of the Fittings at room temperature

		Upper Yield Point ReH (N/mm2) min.		Hardness Test (HRB)
Min.	485	205	35	
Max				

Application/ Usage:

Threaded pipe fittings are commonly used in Water gas pipes, small diameter water pipes, compressed air pipes and lowpressure steam pipes.

SHIJIAZHUANG DEYE PIPING INDUSTRY CO., LTD Pipefittings Department)

